



Design & Materials

Material	Fire-retardant - Nylon 6 v0
Outer Material	Aluminum Body
Cable	3x1,5 mm /180 cm cable (other lengths available)
Mounting	19" 1U or 2U Rack Mountable – Rotating Ears
Contacts	Phase/Neutral Contact Busbar: 1mm (2x0,5mm) 100% Brass Grounding Busbar: 0,5mm 100% Brass
Fuse	16A (options on demand) Other Current Rate Mcb's and circuit protection units are available.
Certificates	CE (Main Power Cord: TSE,VDE,CE Fuse: TSE,CE On/Off Switch: CE)
Varranty	2 Years for materials and workmanship

Highlights:

- CE Certification
- Design Registration
- Rack Mountable
- Rotating Installation Ears
- Fuse Box designed to prevent accidental shutdowns
- Certified Copper Cables
- Fire-retardant plastic material
- 100% Brass 0.5mm socket contacts
- Earthing contacts are TSD and BDE German standard
- Arc flash proof sockets
- Mounting ears create isolation between rack cabinets and PDU

Electrical & Enviromental

Input Connectors	SCHUKO
Maximum Output Power	4000W
Cord Length	1,8 mt
Nominal Input Voltage	100-240V
Maximum total current draw	16 A (Other MCB's Rates and circuit protection units are available)
Output connectors	SCHUKO outlets
Operable Elevation	0-3000 mt
Operable Temperature	-5°C to +45°C
Storage Temperature	-25°C to +65 °C

The Package Includes:

- PDU
- Screw&Nut Set for Installation

Variations:

- Surge Protection
- Multi-meter (Voltmeter & Ammeter)
- Custom Design & Color Options
- Cable Length on demand
- French (UPS) / UK / C13 C19 Sockets

Shipping Information

	Product Name	Box Dimensions	PDU Weight	Box Weight
PDU3SV	19" 1U 3 Way Schuko 16A Fused PDU w/ 3x1,5mm2 Cable	5x10x52cm	747,2gr	893,6gr
PDU6SV	19" 1U 6 Way Schuko 16A Fused PDU w/ 3x1,5mm2 Cable	5x10x52cm	747,2gr	893,6gr
PDU9SV	19" 2U 9 Way Schuko 16A Fused PDU w/ 3x1,5mm2 Cable	10x10x52cm	1218,8gr	1259,8gr
PDU12SV	19" 2U 12 Way Schuko 16A Fused PDU w/ 3x1,5mm2 Cable	10x10x52cm	1263,4gr	1404,6gr

További termékeink >>